

HERBeRT - smith



Feature:

- Precision ground and supersonic frequency hardened bed ways
- 16 speeds all geared headstock
- Foot brake giving rapid braking
- The spindle system is high in rigidity and accuracy



Standard Accessories :

- 3 Jaw Chuck
- Face Plate
- Chip Tray
- Splash Guard
- Steady Rest
- Carriage mounted
- Follow Rest
- R/F control

Optional Accessories :

- DRO (2 Axis)
- Quick change tool post
- Taper turning attachment

Additional for C6236 :

- Work Light
- 4 Jaw Chuck
- Foot Brake
- Coolant System

TECHNICAL DATA

ITEM	C6236
Swing over Bed	356 mm
Swing over cross slide	220 mm
Swing in Gap Diameter	506 mm
Admit between centers	1000 mm
Bed Width	206 mm
Spindle Bore	38 mm
Spindle Nose	D1 - 4
Taper of spindle bore	MT 5
Lead screw dia x Pitch	22 mm
Range of Spindle Speed (rpm)	45 - 1800
Threads - Imperial Pitches	4 - 112 TPI
Threads - Metric Pitches	0.45 - 7.5 mm
Longitudinal feeds (mm/rev)	0.043 - 0.653
Cross feeds (mm/rev)	0.015 - 0.653
Travel of Tailstock quill	120 mm
Diameter of Tailstock quill	45 mm
Taper hole of Tailstock quill	MT 3
Main Motor	1.5 KW / 2.4 KW
Weight	880 Kg

All Geared High Speed Precision Lathes

India's Fastest Selling Lathe **WORLD CLASS**

SHIV MACHINE TOOLS

Website : www.shimato.in Sales : info@shimato.in Service : service@shimato.in

Chennai H.O.:
#102, Armenian Street, Chennai-1
Tel: 044-2522 3473/7305 Fax: 044-25227954
Mob: 99400 28713 / 98401 50000
93802 93852 / 93802 42142

Chennai - Ambattur:
371, SIDCO Industrial Estate,
North Phase (Opp.Godrej Gate No.2)
Chennai-98.
Tel: 044-2635 0060/61 Fax:2635 0062

Pune:
Heera Plaza, J-42-43, Indrayani Nagar Road,
Opp. Simens Cotmac, Bhosari, Pune-26
Tel: 020-27119700 Fax: 020-27112030



