HERBeRT - smith

Feature:

- Precision ground and supersonic frequency hardened bed ways
- The spindle is supported with precision roller bearing
- Headstock gears are made of high quality steel, ground and hardened
- Removable gap is provided for larger diameter work
- Gear box is designed with four independent eas operating drums, and has various feeds and thread cutting function

Standard Accessories:

- 3 Jaw Chuck Change Gears
- M.T.3 Dead Centers- Tool Box And Tools
- Oil Gun Reduction Sleeve MT5/3
- Foot Stands
 Splash Guard
- Oil Tray

Optional Accessories:

- 4 Jaw Chuck
 Face Plate
- Steady Rest Follow Rest
- Work Light Brake System
- Coolant System Live Center
- Drill Chuck + Drill Arbor
- Leadscrew Cover Chuck Guard
- Localizer Clutch For Feed Fod
- Quick Change Tool Post
- Digital Readout (2 Axis)

India's Fastest Selling Lathe



Mary Birl	2.3	
el,		
er	C08210	iA.
easy	-	
TECHNICAL DATA		
ITEN	Λ	CQ6230A-1
Swing over Bed		310 mm
Swing over cross slide		180 mm
Swing in Gap Diameter		450 mm
Admit between centers		910 mm
Bed Width		180 mm
Spindle Bore		38 mm
Spindle Nose		MT 5
Taper of spindle bore		MT 5
Cross Slide Travel		130 mm
Com	pound rest travel	75 mm

Threads - Imperial Pitches 4 - 60 TPI
Threads - Metric Pithches 0.4 - 7 mm

Range of Spindle Speed (rpm) 65 - 1810

Cutting tool max section

Longitudinal feeds (mm/rev) 0.0527 - 1.2912

Cross feeds (mm/rev) 0.014 - 0.276
Travel of Tailstock quill 100 mm

Diameter of Tailstock quill 32 mm

Taper hole of Tailstock quill MT 3

Main Motor 1.1 KW / 1.5 KW

Weight 609 Kg

SHIV MACHINE TOOLS



#102, Armenian Street, Chennai-1 Tel: 044-2522 3473/7305 Fax: 044-25227954

Mob: 99400 28713 / 98401 50000 93802 93852 / 93802 42142 Chennai - Ambattur: 371, SIDCO Industrial Estate, North Phase (Opp.Godrej Gate No.2) Chennai-98.

Tel: 044-2635 0060/61 Fax:2635 0062







Pune:

Heera Plaza, J-42-43, Indrayani Nagar Road, Opp. Simens Cotmac, Bhosari, Pune-26 Tel: 020-27119700 Fax: 020-27112030

14 mm x 14 mm